

INTRODUCTION

SETAQUA 37-3372 (formerly SETAQUA 6472) is an acrylic copolymer emulsion for industrial air dry enamels and maintenance primers. Coatings formulated with SETAQUA 37-3372 exhibit excellent adhesion properties, exterior durability and good stain and water resistance. In addition, SETAQUA 37-3372 is designed to offer good mechanical stability.

TYPE

Acrylic copolymer emulsion

FORM OF DELIVERY (F.O.D.)

40% non-volatile in demineralized water

PRODUCT DATA

Non-Volatile, by wt:	40.0 ± 1.0 %
Viscosity, Brookfield:	100 maximum cps
pH value:	7.0 – 8.0
Density:	8.60 lbs./gal.
Tg:	40°C
Non-volatiles, by vol:	38.0%
Particle size:	100 nm

PERFORMANCE HIGHLIGHTS

- Fast air dry
- Excellent adhesion to metal and wood substrates
- Good water and stain resistance Mechanical stability
- Low VOC enamels at <1.75 lbs/gal

SUGGESTED USES

- Topcoats and enamels
- Durable primers and surfaces for metal
- Clear maintenance coatings

STORAGE

In the original sealed containers, this product is stable for 1 year at temperatures between 40°F and up to 100°F.

PRECAUTIONS

Before using SETAQUA 37-3372, see the Safety Data Sheet (SDS) for information on the identified hazards of the material and the recommended personal protective equipment and procedures.

STORAGE AND HANDLING

Care should be taken to protect from freezing and not to expose the product to high temperature conditions, direct sunlight, ignition sources, oxidizing agents, alkalis or acids. Storage and handling should be in stainless steel, amber glass, amber polyethylene or baked phenolic lined containers. Wash thoroughly after handling. Keep container tightly closed. Use with adequate ventilation. See the SDS for the recommended storage temperature range for SETAQUA 37-3372.