

VISCOPOL™ 9250 is an APEO free acrylic aqueous dispersion.

### SOLVENT

Water

### TYPICAL PROPERTIES

<b>Appearance:</b>	White opaque liquid
<b>Non-Volatiles:</b>	49 %
ISO 3251, <i>STM 001G</i>	
<b>Dynamic Viscosity (Brookfield) DIN EN ISO 2555:</b>	700 mPa.s
DIN EN ISO 2555, <i>ASTM D 2196</i> (2; 50 1/min; 20 °C)	
<b>pH (20 - 25 °C):</b>	8.4
<i>STM 007A</i>	
<b>MFFT:</b>	10 °C
ASTM D 2354, <i>STM 087A</i>	

### TECHNICAL FEATURES

VISCOPOL™ 9250 is an APEO-free acrylic aqueous dispersion, developed specifically for printing ink and paper and board coating applications.

Features include:

- Fast Drying
- Excellent Pigment Wetting
- Solvent Tolerant
- Excellent Water and Grease Resistance
- Good Block Resistance
- Low Foaming
- Excellent Gloss and Adhesion Properties
- Excellent Mechanical Shear Stability

### APPLICATION

VISCOPOL™ 9250 can be used as a vehicle for both flexo and gravure inks, paper and board coatings, and overprint lacquers. Excellent adhesion can be attained on a wide range of substrates, including treated polyolefin, cellophane and polyester films.

### STORAGE

VISCOPOL™ 9250 should be stored under cover, out of direct sunlight and avoiding extreme temperature changes. Under normal storage conditions (5 – 35°C, away from extremes) sealed, unopened containers of this material would have a shelf life of 12 months from the date of manufacture. If stored for longer than 12 months, product must be rechecked for suitability in the intended application.

### SAFETY

Refer to product Safety Data Sheet before handling or use.