

SETAQUA® ECO 9000 has been developed especially for high quality, high gloss interior and exterior emulsion paints with exceptional DPUR (Dirt Pick Up Resistance) durability, gloss, flow for concrete. SETAQUA® ECO 9000 will allow the paint formulator a wide degree of flexibility as it is well suited for use in vinyl, satin, flat and roof paints where its excellent mar resistant properties, durability and flow can be utilized.

TYPE

Pure Acrylic Emulsion

SUGGESTED USES

Water Based Decorative Concrete Paints (Interior and Exterior)

FORM OF DELIVERY (F.O.D)

50.0% non-volatile in w

RECOMMENDED COALESCENT LEVELS:

5.5-6.5% Based on Polymer Solids

PRODUCT DATA

Non-Volatile, by wt:	50.0 ± 1%
Viscosity, Brookfield RVT	
4/50 25oC :	100– 1000 cps
pH.:	8.0 –9.0
Particle Size, micron:	0.12
MFFT, °C	20-22
Appearance :	white, milky and free from extraneous matter
Density:	1.07 ± 0.10 KG/LITER.
Tg, °C	25
Non-volatiles, by vol:	46.7%
Flash Point:	N/A

STORAGE

At temperatures up to 100°F storage stability packed in original containers amounts for 6 months.

PRECAUTIONS

Before using SETAQUA® ECO 9000 , see the Safety Data Sheet (SDS) for information on the identified hazards of the material and the recommended personal protective equipment and procedures.

STORAGE AND HANDLING

Care should be taken not to expose the product to high temperature conditions, direct sunlight, oxidizing agents, alkalis or acids. Storage and handling should be in stainless steel, amber glass, polyethylene or baked phenolic lined containers. Wash thoroughly after handling. Keep container tightly closed. Use with adequate ventilation. This is classified as non-Dangerous Goods for shipping
8/16/2017(replaces all previous versions)

PERFORMANCE HIGHLIGHTS

- High DPUR (Dirt Pick UP Resistance) properties
- Lower coalescent levels but higher DPUR
- Lower VOC formulations