

INTRODUCTION

Ucecryl B 3009 is a high MFFT straight acrylic emulsion copolymer designed for use in paints. Coatings based on Ucecryl B 3009 exhibit a good weathering resistance and a good water repellency.

SUGGESTED APPLICATIONS

Ucecryl B 3009 is recommended for use in paints for fibre cement sheets.

PERFORMANCE HIGHLIGHTS

Ucecryl B 3009 is :
Free of alkylphenol ethoxylates (APEO)
Ammonia-free

UCECRYL B 3009 Product data

Determined per batch:

Appearance (D0201100)	milky liquid
Solids content (2 h at 105 °C) (D0001000)	46.5 - 48.5 %
Brookfield viscosity (At 25 °C - 50 rpm) (D0059500)	<= 200 mPa.s
pH measurement (D0002000)	7.5 - 8.5
Not continually determined :	
MFFT (D0150000)	47 °C

RECOMMENDED FORMULATIONS

Contact us.

STANDARD PACKAGING

Ucecryl B 3009 is available in the following standard packaging:

- Bulk
- 1000 kg one way white PE Schütz container, 3 inch

Any other special packaging should be requested to the sales account representative.

PRECAUTIONS

Appropriate precautions should be taken to avoid eye and skin contact .
Please refer to the Material Safety Data Sheet for further details.

STATUTORY LABELLING

See Material Safety Data Sheet for information.

TRANSPORT REGULATIONS

See Material Safety Data Sheet for information.

STORAGE AND HANDLING

See Material Safety Data Sheet for information.