

INTRODUCTION

A surfactant free aqueous dispersion of acrylic polymers for highly durable furniture finishes and other high performance, industrial wood applications. ECOWISE CHOICE approval in process (contact your allnex representative for more information).

TYPE

Self-crosslinking, surfactant-free, acrylic emulsion

FORM OF DELIVERY (F.O.D)

40% non-volatile in demineralized water

PRODUCT DATA

Non-Volatile, by weight:	40.0 ± 1.0 %
Dynamic Viscosity Brookfield LV #3 spindle, 50 RPM [mPa.s]	1000 maximum
pH value:	7.0 - 9.0
Density:	8.80 ± 0.10 lbs./gal.
MFFT (approx.):	15°C
Appearance:	Clear, free of dirt or grit
Non-volatiles, by volume:	37.3 % (theo.)

PERFORMANCE HIGHLIGHTS

- Exceptional in-can and dry film clarity
- Excellent chemical resistance
- Fast drying and rapid hardness development
- Good block resistance
- Good sandability
- Low VOC formulations (50-100 g/L)
- Excellent global environmental compliance

SUGGESTED USES

- Clear industrial wood lacquers
- Pigmented industrial wood primers and topcoats
- Kitchen cabinet and furniture coatings
- Floor finishes

STORAGE

In the original sealed containers, this product is stable for 9 months at temperatures between 40°F and up to 100°F.

PRECAUTIONS

Before using SETAQUA 6722, see the Safety Data Sheet (SDS) for information on the identified hazards of the material and the recommended personal protective equipment and procedures.

STORAGE AND HANDLING

Care should be taken to protect from freezing. Care should be taken to not expose the product to high temperature conditions, direct sunlight, ignition sources, oxidizing agents, alkalis or acids. Storage and handling should be in polyethylene containers. Wash thoroughly after handling. Keep container tightly closed. Use with adequate ventilation. See the SDS for the recommended storage temperature range for SETAQUA 6722.