

INTRODUCTION

SETAQUA 37-6498 is a high performance, hard acrylic terpolymer for a range of applications including concrete and roof tile coatings.

TYPE

Acrylic emulsion

FORM OF DELIVERY (F.O.D)

45% non-volatile in demineralized water

PRODUCT DATA

Non-Volatile, by wt:	45 %
pH value:	7.7
Viscosity, Brookfield:	100 cps
Density:	8.65 lbs/gal
MFFT:	30° C
Particle Size:	0.10 microns

PERFORMANCE HIGHLIGHTS

- Exceptional exterior durability and hardness
- Excellent adhesion and water resistance
- Passes water retention requirement of ASTM C1315

SUGGESTED USES

- Concrete and roof tile coatings
- Clear glazes and coatings where hardness and durability are required
- Concrete curing membrane

STORAGE

In the original sealed containers, this product is stable for 9 months at temperatures between 40°F and up to 100°F.

PRECAUTIONS

Before using SETAQUA 37-6498, see the Safety Data Sheet (SDS) for information on the identified hazards of the material and the recommended personal protective equipment and procedures.

STORAGE AND HANDLING

Care should be taken to protect from freezing and not to expose the product to high temperature conditions, direct sunlight, ignition sources, oxidizing agents, alkalis or acids. Storage and handling should be in stainless steel, amber glass, amber polyethylene or baked phenolic lined containers. Wash thoroughly after handling. Keep container tightly closed. Use with adequate ventilation. See the SDS for the recommended storage temperature range for SETAQUA 37-6498.