

INTRODUCTION

UCECRYL® BMR 47 is a low MFFT straight acrylic emulsion copolymer designed for use in paints.

PRODUCT DATA

Determined per batch:

Appearance (D0201100)	milky liquid
Solids content (2 h at 105 °C) (D0001000)	54.0 - 56.0 %
Brookfield viscosity (At 25 °C - 50 rpm) (D0059500)	100 - 400 mPa.s
pH measurement (D0002000)	8.0 - 9.0

Not continually determined :

MFFT (D0150000)	2 °C
--------------------	------

STANDARD PACKAGING

UCECRYL® BMR 47 is available in the following standard packaging:

- Bulk
- 1000 kg one way white PE Schütz container, 3 inch

Any other special packaging should be requested to the sales account representative.

SUGGESTED APPLICATIONS

UCECRYL® BMR 47 is recommended for use in high solids paints (base coats) for metal roof tiles.

PERFORMANCE HIGHLIGHTS

- ✓ Alkylphenol ethoxylate (APEO) - Non Intended

RECOMMENDED FORMULATIONS

Contact us.

PRECAUTIONS

Appropriate precautions should be taken to avoid eye and skin contact . Please refer to the Material Safety Data Sheet for further details.

STATUTORY LABELLING

See Material Safety Data Sheet for information.

TRANSPORT REGULATIONS

See Material Safety Data Sheet for information.

STORAGE AND HANDLING

See Material Safety Data Sheet for information.

SHELF LIFE

Standard shelf life is 365 days from the date of manufacturing.
For products still in allnex possession allnex may extend the expiration date of a batch upon re-testing by QC.