

TIRES™ 4777 is an acrylic solution copolymer.

SOLVENT COMPOSITION

Solvent 100

TYPICAL PROPERTIES

Non-Volatiles: ISO 3251, <i>STM 001G</i>	25 %
Viscosity (DIN cup): DIN 53211, <i>STM 012C</i>	35 seconds
Density (at 25°C): DIN 53217	0.93 kg/dm ³
Colour APHA (Lico): ISO 6271, <i>STM 008F</i>	10 APHA
Glass transition point: <i>STM 004F</i>	30 °C

TECHNICAL FEATURES

TIRES™ 4777 is an acrylic solution copolymer, which dries to form films exhibiting excellent adhesion, flexibility, gloss and durability.

APPLICATION

TIRES™ 4777 has been developed specifically for clear sealers applied to OEM concrete roof tiles and is “ready to use” as supplied. For clean-up of spray equipment, use aromatic solvents such as xylol or solvent 100.

STORAGE

TIRES™ 4777 should be stored under cover, out of direct sunlight and avoiding extreme temperature changes. Under normal storage conditions (5 – 35°C, away from extremes) sealed, unopened containers of this material would have a shelf life of 12 months from the date of manufacture. If stored for longer than 12 months product must be rechecked for suitability in the intended application.

SAFETY

Refer to Safety Data Sheet before handling or use.