

TIRES™ 4777 is an acrylic solution copolymer.

### SOLVENT COMPOSITION

Solvent 100

### TYPICAL PROPERTIES

<b>Non-Volatiles:</b> ISO 3251, <i>STM 001G</i>	25 %
<b>Viscosity (DIN cup):</b> DIN 53211, <i>STM 012C</i>	35 seconds
<b>Density (at 25°C):</b> DIN 53217	0.93 kg/dm <sup>3</sup>
<b>Colour APHA (Lico):</b> ISO 6271, <i>STM 008F</i>	10 APHA
<b>Glass transition point:</b> <i>STM 004F</i>	30 °C

### TECHNICAL FEATURES

TIRES™ 4777 is an acrylic solution copolymer, which dries to form films exhibiting excellent adhesion, flexibility, gloss and durability.

### APPLICATION

TIRES™ 4777 has been developed specifically for clear sealers applied to OEM concrete roof tiles and is “ready to use” as supplied. For clean-up of spray equipment, use aromatic solvents such xylol or solvent 100.

### STORAGE

TIRES™ 4777 should be stored under cover, out of direct sunlight and avoiding extreme temperature changes. Under normal storage conditions (5 – 35°C, away from extremes) sealed, unopened containers of this material would have a shelf life of 12 months from the date of manufacture. If stored for longer than 12 months product must be rechecked for suitability in the intended application.

### SAFETY

Refer to Safety Data Sheet before handling or use.