

SETAL® 01-311/63 is a long oil alkyd resin based on soya-bean oil.

SOLVENT COMPOSITION

White spirit

TYPICAL PROPERTIES

Non-Volatiles: ISO 3251, <i>STM 001G</i>	63 %
Viscosity Gardner-Holdt: ASTM D 1545, <i>STM 012A</i>	X - Z1 GH
Colour GARDNER (Lico): ISO 4630, <i>STM 008E</i>	6 Gardner
Acid value (as such): ISO 3682, <i>STM 303A</i>	7 mg KOH/g
Density (at 25°C): DIN 53217	0.94 kg/dm ³

TECHNICAL FEATURES

SETAL® 01-311/63 is a long oil alkyd resin based on soya-bean oil, which exhibits excellent gloss and gloss retention, high durability, adhesion and non-yellowing properties, fast sag-resistant application, and ease of brushing with excellent leveling.

APPLICATION

SETAL® 01-311/63 may be used to formulate premium quality gloss and semi- gloss architectural brushing enamels for both interior and exterior use.

STORAGE

SETAL® 01-311/63 should be under cover, out of direct sunlight and avoiding extreme temperature changes. Under normal storage conditions (5 - 35°C, away from extremes) sealed, unopened containers of this material would have a shelf life of 12 months from the date of manufacture. If it is stored for longer than 12 months, it is recommended that the product is rechecked for suitability in the intended application.

SAFETY

Refer to Safety Data Sheet before handling or use.