

SETAL P700/40 is a medium oil alkyd resin.

SOLVENT COMPOSITION

White Spirit

TYPICAL PROPERTIES

Non-Volatiles: ISO 3251, <i>STM 001G</i>	40 %
Viscosity Gardner-Holdt: ASTM D 1545, <i>STM 012A</i>	Y - Z1 GH
Acid value (on solid resin): DIN 53402, <i>STM 041A</i>	10 mgKOH/g
Colour GARDNER (Lico): ISO 4630, <i>STM 008E</i>	5 Gardner
Density (at 25°C): DIN 53217	0.88 kg/dm ³

TECHNICAL FEATURES

SETAL P700/40 is a medium oil alkyd resin based mainly on soya-bean oil, with excellent colour-retention, sealing properties, holdout, washability and sheen- uniformity combined with good flow and levelling.

APPLICATION

SETAL P700/40 may be used to formulate flat wall finishes, primers, sealers, undercoats and ceiling paints, for application by brush or roller.

STORAGE

SETAL P700/40 should be stored under cover, out of direct sunlight and avoiding extreme temperature changes.

Storage temperature: 5 – 35°C.

SHELF LIFE

Standard shelf life is 365 days from the date of manufacturing.

For products still in allnex possession allnex may extend the expiration date of a batch upon re-testing by QC.

SAFETY

Refer to Safety Data Sheet before handling or use.