

VISCOPOL™ FC37 is an acrylic binder for a 2 pack floor flushing and levelling compound.

SOLVENT COMPOSITION

Water

TYPICAL PROPERTIES

Appearance: STM 017A	White opaque liquid
Non-volatile content: DIN EN ISO 3251	37 %
Viscosity (DIN cup): DIN 53211, STM 012C	20 seconds
pH (20 - 25 °C): STM 007A	9.2
MFFT: ASTM D 2354, STM 087A	10 °C
Particle size: STM 016A	200 nm

TECHNICAL FEATURES

VISCOPOL™ FC37 is a 2-pack floor flushing and levelling compound consisting of a premixed cementitious powder and acrylic binder. VISCOPOL™ FC37 has a low viscosity, is easily sanded, tough, durable, has good impact resistance, and is compatible with most floor covering adhesives & coating.

APPLICATION

VISCOPOL™ FC37 is recommended for patching, flushing and levelling prior to coating or laying coverings.

VISCOPOL™ FC37 is suitable for use on:

- Concrete
- Cement plaster
- Brick
- Fiber cement sheeting
- Timber sheeting
-

Not recommended for application to actively moving joints and any single application exceeding 3mm build.

STORAGE

VISCOPOL™ FC37 should be stored under cover, out of direct sunlight and avoiding extreme temperature changes. Under normal storage conditions (5 – 35°C, away from extremes) sealed, unopened containers of this material would have a shelf life of 12 months from the date of manufacture. If stored for longer than 12 months, product must be rechecked for suitability in the intended application.

SAFETY

Refer to product Safety Data Sheet before handling or use.