

VISCOPOL™ FC37 is an acrylic binder for a 2 pack floor flushing and levelling compound.

### SOLVENT COMPOSITION

Water

### TYPICAL PROPERTIES

|  |                     |
|--|---------------------|
| <b>Appearance:</b><br>STM 017A                     | White opaque liquid |
| <b>Non-volatile content:</b><br>DIN EN ISO 3251    | 37 %                |
| <b>Viscosity (DIN cup):</b><br>DIN 53211, STM 012C | 20 seconds          |
| <b>pH (20 - 25 °C):</b><br>STM 007A                | 9.2                 |
| <b>MFFT:</b><br>ASTM D 2354, STM 087A              | 10 °C               |
| <b>Particle size:</b><br>STM 016A                  | 200 nm              |

### TECHNICAL FEATURES

VISCOPOL™ FC37 is a 2-pack floor flushing and levelling compound consisting of a premixed cementitious powder and acrylic binder. VISCOPOL™ FC37 has a low viscosity, is easily sanded, tough, durable, has good impact resistance, and is compatible with most floor covering adhesives & coating.

### APPLICATION

VISCOPOL™ FC37 is recommended for patching, flushing and levelling prior to coating or laying coverings.

VISCOPOL™ FC37 is suitable for use on:

- Concrete
- Cement plaster
- Brick
- Fiber cement sheeting
- Timber sheeting
- 

*Not recommended for application to actively moving joints and any single application exceeding 3mm build.*

### STORAGE

VISCOPOL™ FC37 should be stored under cover, out of direct sunlight and avoiding extreme temperature changes. Under normal storage conditions (5 – 35°C, away from extremes) sealed, unopened containers of this material would have a shelf life of 12 months from the date of manufacture. If stored for longer than 12 months, product must be rechecked for suitability in the intended application.

### SAFETY

Refer to product Safety Data Sheet before handling or use.