

### INTRODUCTION

UCECRYL B 3030 is a low MFFT styrene acrylic emulsion copolymer. UCECRYL B 3030 is recommended for use in paints for cementitious substrates.

### TYPE

Styrene acrylic emulsion copolymer

### FORM OF DELIVERY (F.O.D.)

50% non-volatile in water

### PRODUCT DATA

Weight solids:	50.0 ± 1.0%
Viscosity (at 25°C, 50 rpm):	300 –1700 mPas
pH:	7.5-9.5
MFFT	<5°C
Appearance	milky liquid

### PERFORMANCE HIGHLIGHTS

Xi-free  
APEO-free

### SUGGESTED USES

- Cementitious substrates

### STANDARD PACKAGING

UCECRYL B 3030 is available in the following standard packaging:

- 18 kg 18K PE open head pail
- 1000 kg one way white PE container
- Any other special packaging should be requested to the sales account representative.

### STORAGE

At temperatures up to 25°C storage stability packed in original containers amounts to at least 365 days.

### PRECAUTIONS

Appropriate precautions should be taken to avoid eye and skin contact .  
Please refer to the Material Safety Data Sheet for further details.

### STORAGE AND HANDLING

Care should be taken not to expose the product to high temperature conditions, direct sunlight, ignition sources, oxidizing agents, alkalis or acids. Storage and handling should be in stainless steel, amber glass, amber polyethylene or baked phenolic lined containers. Wash thoroughly after handling. Keep container tightly closed. Use with adequate ventilation.