

VISCOPOL™ 6992 is a pure acrylic emulsion

SOLVENT

Water

TYPICAL PROPERTIES

Appearance: white opaque liquid

STM 017A

Non-volatile content: 50 %

DIN EN ISO 3251

Dynamic Viscosity (Brookfield) DIN EN ISO 2555: 500 mPa.s

DIN EN ISO 2555, ASTM D 2196
(2; 50 1/min; 25 °C)

pH (20 - 25 °C): 8.5

STM 007A

MFFT: 11 °C

ASTM D 2354, STM 087A

TECHNICAL FEATURES

VISCOPOL™ 6992 is a fine particle size, adhesion promoted, pure acrylic emulsion. Its near ambient hardness allows for a good combination of flexibility and durability.

APPLICATION

VISCOPOL™ 6992 has been specially designed for use in construction applications, where advantage can be taken of its excellent adhesion and water resistance.

STORAGE

VISCOPOL™ 6992 should be stored under cover, out of direct sunlight and avoiding extreme temperature changes. Under normal storage conditions (5 – 35°C, away from extremes) sealed, unopened containers of this material would have a shelf life of 12 months from the date of manufacture. If stored for longer than 12 months, product must be rechecked for suitability in the intended application.

SAFETY

Refer to product Safety Data Sheet before handling or use.